Verge Dock-PRO






Dock-Pro[™] dock gates are designed to prevent people and equipment falling into recessed dock areas, platforms or into service pits.


The practical, compact lift-a-way design has a top and mid rail configuration, which is lifted easily with a lightweight action, nested out of the way which overcomes the need to keep swing areas clear. This is an excellent, space-saving alternative.

Features and benefits

- ✓ OH&S compliant
- ✓ No pinch points
- ✓ Handle for easy lifting
- ✓ Smooth action
- ✓ Space efficient
- Eliminates risk of falling
- ✓ Width options available







Specifications

	Dock-PRO Single – max 3.1m wide	Dock-PRO Bifold - max 3.2m wide
Main post	4mm thick mild steel formed mounting post	
Height	1000mm	
Finish	Zinc plated - powder coated yellow gold	
Fixing	$4 \times M12 \times 80$ through bolts (masonry) M12 \times 50 zinc bolt and nut (platform application)	
Gas strut	$2 \times 100 - 150 - 200$ UM depending on the length of gat	
Top rail	75 x 50 x 3 RAD RHS aluminium. Custom cut to length	
Finish	Powder coated yellow gold	
Mid rail	$50 \times 50 \times 3$ RAD SHS aluminium. Custom cut to length	
Bifold mid post	-	50 x 50 x 3 RAD SHS aluminium 4mm thick bracketing
Fixing	-	4 x m12 x 75 zinc B&N, ploy pivot bush
Finish	-	Powder coated Yellow Gold
End post	50 x 50 x 3 RAD SHS aluminium. 4mm thick bracketing	
Receiver post	4mm thick mild steel formed channel receiver post	
Finish	Zinc plated – powder coated yellow gold	
Fixing	4 x M12 x 80 through bolts	

Verge Dock-PRO





General maintenance


Ensure baseplates are kept free from dirt, dust and grit build-up to prevent premature corrosion. Keep all powder coated surface free from dirt / dust, to eliminate moisture retention. In the event of paintwork damage, this must be touched to prevent corrosion.

Monthly check on bolt and connector tension is recommended, especially the pivoting points.

Keep gas struts clean and free from dust and grit.

Product range


Dock-PRO Single - BV081



Dock-PRO double configuration - BV083



Dock-PRO Bi-Fold - BV082



Dock-PRO Bi-Fold double configuration - BV084

